4 Channel

960H

SA-4100SHE SA-4100SHX



























Front Panel



Rear Panel



SA-4100SHE

Specifications

MODEL		SA-4100SHE	SA-4100SHX	
	Compression Format	Baseline	Baseline H.264	
System	os	Embedded Linux		
Video	Input	4CH Standard BNC		
	Standard Output	VGA,CVBS		
	Advanced Output	HDMI	HDMI Spot	
Audio	Input	4CH	2CH	
	Output	1C	1CH	
	Two way audio	Yes		
Recording	Real-Time Recording	4CH 960H Real-Time		
	HD-SDI	No		
	960H	100/120 FPS (Total)		
	D1	100/120 FPS (Total)		
	CIF	100/120 FPS (Total)		
	Recording Mode	Schedule, Manual, Motion, Sensor		
Playback	Playback Channel	4CH		
	Search Mode	Time, Event, File Management		
Backup	USB	1 USB2.0 port		
	DVD Burner	No		
	Backup Format	DAT or AVI		
Remote Application	Dual Stream	Master stream: 1-25/30 FPS @960H	Network stream: 1-25/30 FPS @CIF	
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)		
	Master Stream in Network	Yes		
	CMS	Yes		
	3G	ProvisionCAM for iPad/iPhone/Blackberry/Android/Symbian/Windows Mobile		
	User Access	10 users online with professional authority management		
Alarm	Input	4CH	No	
	Output	1CH	No	
Storage	HDD	1SATA (3TB)		
	E-SATA	No		
PTZ	Connection	1 x RS485		
	Supported Protocol	Pelco D, Pelco P, Samsung, Visca		
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus		
Network	Ethernet	100 Mbps (RJ-45)		
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP		
Others	Dimension	300(W) x 260(D) x 55(H) mm		
	IR Controller	Yes		
	Power Supply	DC12V/2A		
	Operating Temperature	0°C ~50°C		